

Seamless Steel Tubing According To API – 5 CT - type 1 RANGE 2

Item	Tubing	Grade	Nominal Weight (lb/ft)	Thread and Coupling	Qty (meter)
1	3 1/2"	L - 80	9.2	Vam Top or equivalent	10000
2	2 7/8"	L - 80	6.4	Vam Top or equivalent	8000
3	COUPLING 3 1/2 "	L - 80	9.2	Vam Top or equivalent	(pcs- 25)
4	COUPLING 3 1/2 "	L - 80	9.3	EUE	(pcs- 25)
5	3 1/2"	L - 80	9.2	Vam Top or equivalent	(pcs-10) 2m
6	3 1/2"	L - 80	9.2	Vam Top or equivalent	(pcs-10) 3m
7	3 1/2"	L - 80	9.3	EUE	(pcs-10) 2m
8	3 1/2"	L - 80	9.3	EUE	(pcs-10) 3m

Gross - Over			
Item	Grade	Description	Qty (pcs)
9	L - 80	3 1/2 " VAM Top or equivalent PIN x 3 1/2 " EUE PIN	30
10	L - 80	3 1/2 " VAM Top or equivalent PIN x 2 7/8 " VAM Top or equivalent PIN	15
11	L - 80	3 1/2 " EUE PIN x 2 7/8 " VAM Top or equivalent PIN	15

Note:

Inside Diameter tubing and connections (2 7/8") ID= 62 mm= 2.4409"

Drift= 2.347"

Inside Diameter tubing and connections (3 1/2") ID= 76 mm= 2.992"

Drift= 2.867"

Remarks

- 1- For items (4-7-8-9-11) Valid API-5CT should be enclosed with the offer. includes the following :the manufacturer of(tubing plain end and coupling and thread) . processor of (tubing plain end and coupling and thread).
- For items (1-2-3-5-6-10) Valid API-5CT should be enclosed with the offer. includes the following : (the manufacturer of tubing plain end, . processor of tubing plain end).
- 2- the bidder can submit Vam Top or equivalent Vam Top to be interchange 100% with Vam Top thread inclosing the needed attached certificates , with the offer (an authorize from Valuric. Co to manufacturing this type of thread)
- 3- the bidder should be mention the name of Vam Top thread manufacturer or equivalent Vam Top thread manufacturer if the pipes manufacture doesn't make this thread
- 4- Mill inspection hydrostatic and pressure test are requested and should be Acc to API- 5CT
- 5-Each Pipe will be supplied with internal and external closed end protectors.
- 6- pipe should be coated with varnish coating for long time storage to protect them from the rust and corrosion
- 7- Clearly marketing should be typed on the pipes body including(tubing manufacturing, ,origin country , OD ,grade, weight lb/ft , heat number ,heat treatment, pipe long , type of thread , and all other specification Acc to API- 5CT
- 8- Mill test and inspection certificate must be included with shipping documents.
- 9- the manufacturer should provide analysis license for tubing metal with shipment .
- 10-Valid ISO certificate for equivalent Vam Top thread manufacturer
- 11- catalog or technical sheet for the offered thread from the manufacturer should be enclosed with the offer
- 12- origin country and the manufacturer should be mentioned .
- 13- The materials should be new , not renewed.

14-Certificate issued by neutral international inspection company approved by the Syrian petroleum Company stating That the materials are conforming with specifications and API standards and tests specified in tender book with the shipment.

15-The maximum number of manufacturers allowed is only two for all materials.

16- All tubulars should be shipped in bundles.